





DESCRIPTION

The **360 freestanding screen** is a divider element as well as a decorative element for the work environment. The panels are made of 25mm MFC board + 5mm of polyurethane foam, density 60kg / m³ on each side of the MFC Board, which contributes to improve the acoustic comfort of the area where it is allocated. The screens incorporate a robust system of rotation that allow the panels to rotate 360° , being able to orientate them according to the needs of the user and situation. The whole set rests on a 80x28cm and 6mm thick steel base that provides a great stability of the screen during the rotations. In addition, the base incorporates felt pads to move the module without damaging the floor.

FEATURES

FLEXIBLE PROFILE UPHOLSTERED DIVIDER e= 35 mm

- 1 25mm melamine board
- 2 5mm foam on each side. Density of foam: 60kg / m³.
- 3 Available in all "T" and "M" fabric range
- 8mm thick flexible Profile
- **(5)** Robust system of rotation fixed to the base that allows 360° rotation of the screen.
- 80x28cm base made of 6mm thick steel. Painted with epoxy paint in White, Silver or Black.
- 7 Felt pads on the base.


FINISHES (see finishes card)

SCREEN FINISH

Fabric T - Newport



DIMENSIONS (cm)



BASE FINISH



48,51%

RECYCLED MATERIALS

100%

ALUMINIUM, STEEL & W00D

100%

RECYCLABLE

PACKAGE AND THINNER

FREE

EASY

TO CLEAN AND MAINTAIN



MATERIALS

Maximum use of materials to eliminate and minimize scraps. Use of recyclable and recycled materials in those components that do not affect the functionality and durability.



PRODUCTION

Maximum optimization of energy use. Minimal environmental impact. Last generation technological systems. Zero discharge of wastewater. No VOC coatings. Processes free of heavy metals, phosphates, OC and COD.



TRANSPORT

Detachable systems. Volumes that facilitate the optimization of space. Maximum reduction of energy consumption by transport.



USE

Quality and warranty. Long lasting. Replacements available.



DISPOSAL

Waste reduction. Supplier-manufacturer packaging reuse system. Components are easy to be separated. Inks in packaging are water-based, without solvents.



CERTIFICATES AND REFERENCES

AENOF

The different programmes get points in different environmental categories to get the LEED certificate (sustainability, material and resources, water, energy and atmosphere, inner environment quality, innovation and design).







ISO 14001 Certificate



E1 Certificate by EN 13986



California 93120



ACTIU TECHNOLOGY PARK LEED® PLATINUM certified by USGBC Leadership in Energy & Environmental Design LEED® Odd certified 2011 - LEED® Platinum certified 2017