



Composizione: 88% Pvc, 6% Pl, 6% Co

Test

- Solidità alla luce: 7, UNI ISO 4582/4892
- Resistenza alla fiamma: UNI 9175 classe 1IM, EN 1021:2014 part 1, EN 1021:2014 part 2, BS 5852 IS 0, BS 5852 IS 1
- Navale: FTP Code 307(88):10 Annex 1 part 8, ex IMO res. A652 (16)

Martindale: 100.000 cicli, UNI EN ISO 5470-2

Lavaggio: spolverare delicatamente e in caso di macchie lievi passare la superficie con un panno umido risciacquando con acqua, senza strizzare

Applicazioni: rivestimento per imbottito contract

Colore: possono riscontrarsi lievi differenze

Composition: 88% Pvc, 6% Pl, 6% Co

Test

- Lightfastness: 7, UNI ISO 4582/4892
- Flammability: UNI 9175 classe 1IM, EN 1021:2014 part 1, EN 1021:2014 part 2, BS 5852 IS 0, BS 5852 IS 1
- Nautical: FTP Code 307(88):10 Annex 1 part 8, ex IMO res. A652 (16)

Martindale: 100.000 cycles, UNI EN ISO 12497-2

Washing: dust gently and in case of light stains pass the surface with a damp cloth rinse with water without squeezing

Application: contract upholstered furniture

Colour: little difference may occur

Category: L B

