

VIVA

— By Alegre Design —



■ DESCRIPTION

Viva shell is manufactured with SEBS double layer padded injection on the rigid Polypropylene (P.P) shell with mineral particles (SEBS Shell, 1/2" thickness) SEBS material provides a padded surface soft to the touch and an optimum hardness to resist an intensive use. It is a material with high water resistance (hydrolysis) and easy to clean. It keeps all chemical capabilities including the colour intensity against and extended Sun exposure (UVI effect). SEBS is a material without PVC, for that reason takes care of user's health and the environment Ø 3/4" Steel tube and 1/4" thickness frame. Chromed Silver, and white finishes. Black polypropylene (P.P) glides. It includes stacking caps (stacking maximum 5 units).

■ BACK AND SEAT




(see finishes and fabric card)



■ SIZES

Total height: from 32 3/4"
 Total width: from 20 3/4"
 Total depth: from 21 1/4"

■ SIZES



- ① SEBS system double layer padded injection
- ② Polypropylene (P.P) Shell with mineral particles (SEBS shell, 1/2" thickness)
- ③ Stacking caps
- ④ Ø 3/4" steel tube and 1/4" thickness
- ⑤ Polypropylene (P.P) glides

■ **DESCRIPTION**

Viva shell is manufactured with SEBS double layer padded injection on the rigid Polypropylene (P.P) shell with mineral particles (SEBS Shell, 1/2" thickness) SEBS material provides a padded surface soft to the touch and an optimum hardness to resist an intensive use. It is a material with high water resistance (hydrolysis) and easy to clean. It keeps all chemical capabilities including the colour intensity against and extended Sun exposure (UVI effect). SEBS is a material without PVC, for that reason takes care of user's health and the environment. Ø 3/4" **Steel** tube and 1/4" thickness frame. Chromed Silver, and white finishes. Black polypropylene (P.P) glides.

■ **BACK AND SEAT**




(see finishes and fabric card)

■ **SIZES**

Total height: from 32 3/4"
 Total width: from 20 3/4"
 Total depth: from 21 1/4"

■ **SIZES**



- ① SEBS system double layer padded injection
- ② Polypropylene (P.P) Shell with mineral particles (SEBS shell, 1/2" thickness)
- ③ Ø 3/4" steel tube and 1/4" thickness
- ④ Polypropylene (P.P) glides



MATERIALS

Maximum use of materials to eliminate and minimize scraps. Use of recyclable and recycled materials in those components that do not affect the functionality and durability.

35,31%
RECYCLED
MATERIALS



PRODUCTION

Maximum optimization of energy use. Minimal environmental impact. Last generation technological systems. Zero discharge of wastewater. No VOC coatings. Processes free of heavy metals, phosphates, OC and COD.

100%
RECYCLABLE
ALUMINIUM, STEEL
& WOOD



TRANSPORT

Detachable systems. Volumes that facilitate the optimization of space. Maximum reduction of energy consumption by transport.

100%
RECYCLABLE
PACKAGE AND THINNER
FREE



USE

Quality and warranty. Long lasting. Replacements available.

EASY
TO CLEAN
AND MAINTAIN



DISPOSAL

Waste reduction. Supplier-manufacturer packaging reuse system. Components are easy to be separated. Inks in packaging are water-based, without solvents.

97,15%
RECYCLABLE
MATERIALS

CERTIFICATES AND REFERENCES

The different programmes get points in different environmental categories to get the LEED certificate (sustainability, material and resources, water, energy and atmosphere, inner environment quality, innovation and design).



STANDARDS

VIVA has passed tests done in our technical department as well as the tests done in AIDIMA the Technological Institute for furniture. The tests correspond to:

4 Legs. Standard applied

- **UNE-EN 16139:13.** Furniture. Resistance, long lasting, security. Requirements for non domestic use seating.

Beam Seating. Standard applied

- **UNE-EN 15373:07.** Furniture. Resistance, long lasting, security. Requirements for non domestic use seating.

- **UNE-EN 1022:05.** Office furniture. Confident chairs.

- **UNE-EN 1728:00.** Domestic furniture - Seating - Test methods for the determination of strength and durability.